



Put your trust in the highest quality flexible coatings, sealants and adhesives on the market!

PLASTIDIP UK LIMITED

Unit 1, Harvesting Lane, East Meon, Hampshire, GU32 1QR.
United Kingdom.

Sales: 0044 (0)1730 823823

Technical: 0044 (0)1730 823123

Fax: 0044 (0)1730 823321

E.mail: sales@plastidip.co.uk

Web: www.plastidip.co.uk

Chameleon Flake Instructions

Application Process:

- 1) Prepare as normal
- 2) Apply 3-4 coats of Plastidip Multi Purpose Coating
- 3) Stir Flakes thoroughly into Glossifier or Clear Matt Plastidip
- 4) Apply the Flake Mixture, allowing approximately 20 to 30 minutes drying time between layers, until you achieve the desired effect
- 5) If you wish... Apply a final coat of Glossifier without Flake to achieve a high gloss finish and to protect the Flake coat.

Tips:

- In order to prevent clogging use a 1.4mm nozzle size or above with your spray gun
- As a guide only; mix 30 grams Flake per 1 litre of Glossifier/Plastidip
- The density of the Flake coat can be altered by increasing the ratio of Chameleon Flake per litre
- Agitate the mixture regularly during the spraying process to ensure the flakes are evenly distributed
- If you require help with your spraying technique there are many tips available on YouTube.
- We would advise that you spray a test piece before embarking on your project to ensure the desired effect is achieved