

\*Estimate N/A-Not Applicable N/R-Not Restricted N/E-Not Established

## **MATERIAL SAFETY DATA SHEET**

NOTE: BLANK SPACES ARE NOT PERMITTED	. IF ANY ITEM	IS NOT APPLICABLE, T		I BE MARKI	ED TO INDICATE THAT.		
IDENTITY				PART NO.			
(As shown on Label or package) F-992 High Gloss Clear Lacquer				IF APPLICABLE			
SECTION I							
MANUFACTURER'S EMERGENCY							
NAME Plasti Dip International, Inc.				PHONE No. 1-800-424-9300			
ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE)				REVISION # 0001			
3920 Pheasant Ridge Drive							
2,70				MANUFACTURER'S PHONE			
Blaine, MN 55449				No. FOR INFORMATION 1-763-785-2156			
	DATE MSDS						
	WAS PREPARED April 2, 2015						
SECTION II - HAZARDOUS INGREDIENTS INFO	SECTION II - HAZARDOUS INGREDIENTS INFORMATION. All Health Hazards which comprise 1% or greater of the composition and all						
carcinogens if 0.1% of the composition or greater.	JRIMITION, III	i iicaitii iiazai us wiicii coi	iipiise 170 or grea	iter of the con	iposition and an		
HAZARDOUS COMPONENTS CHEMICAL and	% Wt.	CAS NO.	OSHA	ACGIH	OTHER LIMITS		
IDENTITY AND COMMON NAME (S)	(OPTIONAL		PEL	TLV	RECOMMEND		
Toluene	35-45	108-88-3	200 ppm	50 ppm	RECOMMEND		
Xylene	35-45	1330-20-7	100 ppm	100 ppm			
Ethyl Benzene	10-15	100-41-4		100 ppm 100 ppm			
		100-41-4	100 ppm	100 ppm			
SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS							
BOILING	<b>SPECIFIC GRAVITY</b> $(H_20 = 1)$		APPROXIMATE WEIGHT PER GALLON (LBS)				
POINT 232°F	0.86		7.21				
VAPOR PRESSURE	VAPOR DENSITY		EVAPORATION RATE				
22 mmHg @ 20°C	(AIR = 1) Heavier than air		(BUTYL ACETATE =1) > 1.0				
SOLUBILITY IN WATER	% VOC; Xyle		OTHER				
Insoluble		ene 37.5%	(IF ANY) None				
	Ethy	dbenzene 10.3 %					
APPEARANCE							
AND ODOR Characteristic Solvent Odor							
SECTION IV-FIRE AND EXPLOSION HAZARD DATA							
FLASH POINT 45.0°F		AMMABLE LIMITS	LEL		UEL		
(METHOD USED) TCC			1.2		7.0		
EXTINGUISHING							
MEDIA Carbon Dioxide, Dry Chemical, or Foam							
SPECIAL FIRE							
FIGHTING PROCEDURES Self contained breathing apparatus with a full face piece, operated in pressure demand or other positive pressure mode.							
UNUSUAL FIRE AND							
<b>EXPLOSION HAZARDS</b> This material is flammable and may be ignited by heat, sparks, flame or static electricity.							
HAZARDOUS PRODUCTS FORMED BY							
FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide.							
EXPLOSIVE LIMITS							
(% BY VOLUME IN AIR) 1.2 – 7.0							
SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION							
HAZARD RATING		National Fire Protection	on Association (N	FPA)			
4-EXTREME							
3-HIGH	FIRE 3 REACTIV	FIRE 3 REACTIVITY 0.					
2-MODERATE							
1-SLIGHT							
0-INSIGNIFICANT	HEALTH 2 S	HEALTH 2 SPECIAL HAZARDS None .					
**SEE SECTION IV							

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



GEOTION VI. DE LOTIVITY AND OTABILITY DATA						
SECTION VI - REACTIVITY AND STABILITY DATA						
STABILITY UNSTABLE STABLE X CONDITIONS TO AVOID None						
INCOMPATIBILITY (Materials to Avoid) Strong acids, bases, oxidizing agents, selected amines with alkali metals and halogens.  HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide, Carbon Dioxide						
HAZARDOUS DECOMI OSITIC	MAY OCCUR CONDITIONS TO AVOID					
POLYMERIZATION		None				
SECTION VII - HEALTH HAZA						
ROUTES OF ENTRY INHALATION? Yes SKIN? Yes INGESTION? Yes EYES? Yes						
HEALTH ACUTE X See Signs and Symptoms of Exposure below.						
HAZARDS CHRONIC	X Brain and Nervous System Damage (Referred to as solvents or painters syndrome). Drying or Cracking skin.					
CARCINOGENICITY: No	11   2)vvg- (					
SIGNS AND						
SYMPTOMS OF	Headache, Dizziness, Drowsiness, Fatigue, Irregular Heartbeat, Skin and Eye Irritation.					
EXPOSURE	Target Organs: CNS, CVS, PNS, Liver, Kidneys, Lungs, Respiratory System, Skin.					
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Pre-existing Heart, Liver, Kidney and Lung disorders.						
EMERGENCY AND Ingestion: Contact Physician or Poison Control Immediately.						
FIRST AID	Inhalation: Remove to fresh air. Administer Oxygen or Artificial Respi	ration if Necessary				
PROCEDURES	Eye Contact: Flush with large amounts of water. If irritation persists, co					
TROCEDORES	Skin: Wash with soap and water.					
SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE						
SECTION VIII TIMESTETION	, TORISHE HER BER (GIRE) COE					
STEPS TO BE TAKEN	Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers.					
IN CASE MATERIAL IS	Eliminate all sources of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material to dam					
RELEASED OR SPILLED	or contain spills. If large spill, notify appropriate state and local agencies.					
WASTE DISPOSAL METHODS	Dispose of product in accordance with local, county, state and federal regu	ılations.				
PRECAUTIONS TO BE	Keep away from sparks, flame and heat sources. Do not store above 120°F and use adequate ventilation.					
TAKEN IN HANDLING	Avoid inhalation of vapors and contact with liquid product. Use good personal hygiene.					
AND STORAGE						
OTHER	Keep Container Closed When Not In Use. Containers should be disposed of in an environmentally safe manner					
PRECAUTIONS in accordance with Governmental Regulations.						
SECTION IX - CONTROL MEA		PROMEOTRIE OF OVERS				
	(SPECIFY TYPE) Depending on the Airborne concentration, use a	PROTECTIVE GLOVES				
	priate NIOSH approved cartridge and cannister, or supplied air equipment					
VENTILATION LOCAL EXHAUST Supplemental (if needed)  MECHANICAL (GENERAL) To maintain exposure below PEL's		SPECIAL None				
EYE PROTECTION	IECHANICAL (GENERAL) To maintain exposure below PEL's OTHER None OTHER PROTECTIVE CLOTHING OR EQUIPMENT					
· · · · · · · · · · · · · · · · · · ·						
Chemical splash goggles or approved eye protection. Impervious Clothing/Boots as needed.  WORK HYGIENIC PRACTICES Wash thoroughly after handling.						
SECTION X - TRANSPORTATION						
D.O.T. PROPER SHIPPING NAM		RD CLASS 3, PG II				
F A "CONSUMER COMMODITY ORM-D", WHAT IS THE HAZARD CLASS 3, PG II						
D.O.T. I.D. No. (N/U OR N/A) UI						
IATA PROPER SHIPPING NAME Coating Solution IATA HAZARD CLASS 3, PG II IMO No. N/A						
SECTION XI - 313 SUPPLIER NOTIFICATION						
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE						
EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight).						
Toluene, Xylene, Ethyl Benzene						
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH						
DEFECTS, OR OTHER REPRODUCTIVE HARM.						
This is the "back" when printed in dupley Page 2 of 2 pages if not dupley						

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By: Mark Kenow